## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Leonardo
---

Supplier's address: Sompex GmbH & Co. KG, Werftstraße 20-22, 40549 Düsseldorf, DE

Model identifier: 76032

<b>T</b>	- 6	10 - 1- 1		
IVna	$\alpha$ T	IIσnt	source:	,
IVDC	vı	HEILL	Jourte.	

Type of light source:						
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap	o-type	MTC 2835 SMD & 3030 SMD				
(or other electri	(or other electric interface)					
Mains or non-mains:		NMLS	Connected light source (CLS):	No		
Colour-tuneable	Colour-tuneable light source:		Envelope:	-		
High luminance	light source:	No				
Anti-glare shield	Anti-glare shield:		Dimmable:	Yes		
		Product para	meters			
Parameter		Value	Parameter	Value		
		General product p	arameters:			
	nption in on- 00 h), rounded st integer	2	Energy efficiency class	G		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		118 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700 or 3 000		
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	1,4	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	83		
Outer dimen-	Height	75	Spectral power dis-	See image		
sions without	Width	75	tribution in the	in last page		
separate con- trol gear, light- ing control		2	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,464			
		nates (x and y)	0,420			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	8	Survival factor	1,00			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

